

THE SULLAIR BACKFILL TAMPER

THE SULLAIR MBT-6 BACKFILL TAMPER GIVES YOU ALL THE POWER FOR COMPACTING AT A SPEED WHICH ALLOWS COMFORTABLE CONTROL.

Applications

The Sullair MBT-6 backfill tamper is the ideal tool for compacting backfill around utility poles, foundations and other structures. It quickly and efficiently compacts backfill soil excavated to perform service line repair before patching the pavement.

Rotatable Exhaust Deflector

A durable molded exhaust deflector aims the exhaust away from the operator.

Standard Steel Butt

A 6" diameter solid steel butt is standard. Optional butts for special applications are available. The butt is held onto the piston rod with a hex head clamp screw for ease of assembly and removal.

Chrome Plating

Smooth, chrome plated barrel promotes easy clean-off of backfill materials.

Minimal Lubrication Required

With the design features and premium materials of the MBT-6, normal oil carry-over from the compressor, combined with the moisture in the air, will supply sufficient lubrication under normal operating conditions.

No Packing Adjustment

There is no packing adjustment necessary for the Sullair MBT-6. The double seals retain their effectiveness for the life of the packing.

One-Year Limited Warranty

All tamper parts are warranted for one year against manufacturing defects. Additionally, should any part, excluding the butt and buttclamp screw, wear out during normal operation, it is covered by Sullair's exclusive warranty.



Backfill Tamper Butts, like all Sullair accessories, are made specifically for Sullair tools, so proper fit and performance are assured. Our selection includes: (1) 6" Malleable Iron, (2) 6" Steel Butt (standard), (3) 4" Aluminum Butt, (4) Pole Butt Half Moon and (5) 3" Aluminum Butt.

MBT-6 TAMPER SPECIFICATIONS

Net Weight	40½ lbs.
Length	48¾"
Shipping Weight	44 lbs.
Bore and Stroke	1½" X 5½"
Blows per Minute	500
Air Consumption	32 cfm
Air Inlet	¾" FNPT
Butt Diameter	6"



MBT-6