

SULLAIR MDT-30 DEMOLITION TOOLS

THE MDT-30 HAS RELIABLE SCREW-ON RETAINER (NO SPRINGS) AND UTILIZES STANDARD 11 X JUMBO RIVET BUSTER STEEL, SLEEVES AND BUMPERS. ONE YEAR WARRANTY, EXCLUDING WEAR ITEMS, SLEEVES AND BUMPERS.

Two Bolt Backhead

This unique design reduces handle breakage. The common problem of a threaded handle-to-barrel connection coming loose and damaging the handle and internal parts is therefore eliminated.



D-Handle

The strong "D" configuration is large enough to provide a comfortable, sure grip even for a gloved hand.

Minimal Lubrication Required

With its unique design and materials, normal oil carry-over from the compressor, combined with moisture in the air, will usually provide sufficient lubrication under normal operating conditions.

Smoother Operation

The Sullair demolition tool's unique design results in greater operator comfort.

Stroke Length

The piston has been sized relative to the length of the stroke to provide an improved weight/power ratio.

Air Inlet Option


Two air inlet bushings are furnished: 3/8" NPT and 7/8"-24, internal thread. The bushings provide for versatile hose connections while protecting the handle inlet threads.

Exhaust Deflector

Directs exhaust air away from the operator and provides a comfortable grip. It also greatly decreases the sound level of the tool.

MDT-30 DEMOLITION TOOL SPECIFICATIONS

Net Weight	33 lbs.
Length	24.5"
Shipping Weight	35.6 lbs.
Bore and Stroke	1.4 X 7.4"
Blows per Minute	1000
Air Consumption	37.1
Air Inlet Diameter	3/8" NPT or 7/8"-24
Shank	11 X Jumbo
Retainer	Screw-on



MDT-30 uses 11X Jumbo steel.

 **SULLAIR**
www.sullair.com

SULLAIR CORPORATION, 3700 East Michigan Blvd., Michigan City, IN 46360 Telephone: 1-800-SULLAIR or 1-219-879-5451 Fax: 1-219-874-1504