

THE SULLAIR MRD-55 ROCK DRILL

ALL-PURPOSE, HEAVY-DUTY, ROCK DRILL FOR HOLES UP TO 20 FEET DEEP IN THE HARDEST ROCK. FAST ROTATION FOR HIGH PRODUCTIVITY. SWIVEL AIR AND WATER INLET CONNECTION. MINIMAL PARTS CONVERT DRILL FROM DRY FOR GENERAL DRILLING TO WET FOR DUSTLESS DRILLING.

Rubber Handle Grips

Reduce vibration, lessening operator fatigue.

One Control for Drilling and Blowing

The single throttle lever controls all tool functions from off, to blowing only, to progressive drilling speeds.

Adjustable Throttle Control

Allows variable speed control for maximum drilling production.

Continuous Hole Cleaning

Blowing air is directed through the drill rod at all drilling speeds to clear debris from the hole.

Reversible Rotation Pawls

Lengthens life for increased productivity.

Replaceable Chuck Bushing, Piston Cushion Bushing, and Rifle Nut

Ease of replacement extends tool life.

Front Exhaust

Cleaner operating conditions.

90-Day Parts Warranty

This Sullair warranty covers all tool parts against manufacturing defects.

Wet or Dry

Optional "Wet Kit" available for dustless drilling.

Lubrication

MRD-55 Rock Drill requires a constant feed inline oiler (option).

MRD-55 ROCK DRILL SPECIFICATIONS

Net Weight	56 lbs.
Length	23 ³ / ₄ "
Bore and Stroke	2 ⁵ / ₈ " x 2 ¹ / ₁₆ "
Blows per Minute	1650
Air Consumption	95 cfm
Air Inlet	3/4" NPT
Shipping Weight	60 lbs.
Chuck Size	1" HX x 4 ¹ / ₄ " 7/8" HX x 4 ¹ / ₄ "



MRD-55